



THAMES STOCKHOLDERS

LB4

LEADED BRONZE ALLOY

Page: 1 of 1



Product Overview

LB4 is a continuously cast leaded bronze alloy which finds typical use in non-critical bearing applications under low loads.

The alloy includes 5% tin and 9% lead and benefits from good corrosion and wear resistance with reasonable ductility and good machinability. The product is classed as a general-bearing alloy and finds suitability in environments where positioning issues and a lack of lubrication are present. LB4 provides medium overall strength.

Availability:

- Bar

Applications

- Shafts & bushes
- Non-critical, low-load applications
- Light load bearings
- Pump impellers

Key Features

- Good wear & corrosion resistance
- Medium strength
- Good machinability
- Reasonable ductility

* Chemical Composition (weight, %)

	Cu	Sn	Zn	Pb	P	Ni	Sb	Fe	Al	Mn	Si	S	Others
Min.	Rem	4.00		8.00									
Max.	Rem	6.00	2.00	10.00	0.10	2.00	0.50	0.25	0.01	0.20	0.02	0.10	0.50

* Properties as per BS 1400

* Mechanical Properties

	Sand Cast	Chill Cast	Continuous Cast	Centrifugal Cast
Ultimate Tensile Strength	160 N/mm ²	200 N/mm ²	230 N/mm ²	220 N/mm ²
0.2% Proof Strength	60 N/mm ²	80 N/mm ²	130 N/mm ²	80 N/mm ²
Elongation	7%	5%	9%	6%

* Properties as per BS 1400 (minimum unless stated)



Thames Stockholders

Unit 5W, Woodall Road, Redburn Industrial Estate
Ponders End, Enfield, Middlesex EN3 4LQ

Tel: +44 (0)20 8805 3282



SCAN ME



sales@thamesstock.com



www.thamesstock.com

All information in our data sheet is based on approximate testing and is stated to the best of our knowledge and belief. It is presented apart from contractual obligations and does not constitute any guarantee of properties or of processing or application possibilities in individual cases. Our warranties and liabilities are stated exclusively in our terms of trading.